10

15

20

25

30

35

WE CLAIM:

- A system for inspecting a specimen, comprising:
 - a light energy source;
- a multiple element arrangement for receiving light energy from said light energy source;
- a lensing/imaging arrangement for receiving light energy from said multiple element arrangement and imparting said light energy to said specimen;
- a pinhole mask for receiving light energy reflected from said specimen through said lensing arrangement and selectively passing said reflected light energy; and
- a time delay and integration charge coupled device for receiving light energy from said pinhole mask.
- 2. The system of claim 1, wherein said light source comprises a multiple wavelength laser and said multiple element arrangement comprises a fly lens array.
 - 3. The system of claim 1, wherein said light source comprises an arc lamp and said multiple element arrangement comprises a pinhole array.
 - 4. The system of claim 1, wherein said light energy source comprises a laser and said system further comprises a beam expander which receives light energy from said laser and expands light energy toward said multiple element arrangement.
 - 5. The system of claim 2, wherein said fly lens arrangement comprises a plurality of offset individual lenses.
 - 6. The system of claim 5, wherein said fly lens arrangement is substantially aligned with respect to the pinhole mask.
 - 7. The system of claim 1, wherein said lensing/imaging arrangement comprises:
 - a first lens;

15

a transmitter/reflector;

an objective; and

a tube lens.

- 8. The system of claim 1, wherein said lensing/imaging arrangement comprises autofocus capability.
 - 9. The system of claim 1, wherein said pinhole mask is mounted adjacent to said time delay and integration charge coupled device.
 - 10. The system of claim 8, further comprising a focusing lens, wherein said focusing lens receives light energy from said pinhole mask and focuses light energy onto said time delay and integration charge coupled device.
 - 11. The system of claim 1, wherein said light energy source comprises a multiple wavelength slit laser.

12. A specimen inspection system, comprising:

a light energy source;

a multiple element arrangement for receiving energy from said energy source and selectively passing the light energy received;

a lensing arrangement comprising an autofocus system for measuring and cancelling topographical variations during inspection; and

a pinhole mask for filtering light energy received from said lensing arrangement.

13. The specimen inspection system of claim 12, wherein said lensing arrangement receives light energy from said multiple element arrangement and imparts light energy onto a specimen.

30

25

17

25

30

35



- 14. The specimen inspection system of claim 13, wherein said lensing arrangement further transmits light energy reflected from said specimen to said pinhole mask.
- 5 15. The specimen inspection system of claim 12, wherein said light energy source comprises a laser and said multiple element arrangement comprises a fly lens array.
- 16. The specimen inspection system of claim 12, wherein said light energy source comprises an arc lamp and said multiple element arrangement comprises a pinhole array.
 - 17. The specimen inspection system of claim 12, wherein said light energy source comprises a laser and said system further comprises a beam expander which receives light energy from said laser and expands light energy toward said multiple element arrangement.

18. The specimen inspection system of claim 13, wherein said fly lens arrangement comprises a plurality of offset individual lenses.

- 19. The specimen inspection system of claim 15, wherein said fly lens arrangement is substantially aligned with respect to the pinhole mask.
- 20. The specimen inspection system of claim 12, wherein said lensing arrangement comprises:
 - a first lens;
 - a transmitter/reflector;
 - an objective; and
 - a tube lens.
- 21. The specimen inspection system of claim 12, further comprising a time delay and integration charge coupled device for receiving light energy from said pinhole mask.

20211343v1

C

22. The specimen inspection system of claim 12, wherein said pinhole mask is mounted adjacent to a time delay and integration charge coupled device.

oul

23. The specimen inspection system of claim 21, further comprising focusing lens, wherein said focusing lens receives light energy from said pinhole mask and focuses light energy onto said time delay and integration charge coupled device.

10

15

20

25

24. A system for inspecting a semiconductor wafer specimen, comprising:

illumination means for generating light energy;

multiple element passing means for selectively filtering and passing energy received from said illumination means;

lensing means for imparting light energy onto said semiconductor wafer specimen;

masking means for further selectively filtering and passing energy received from said lensing means; and

a time delay and integration charged coupled device for receiving light energy from said masking means.

- 25. The system of claim 24, further comprising autofocus means for measuring and cancelling topographical variations during inspection, said autofocus means operating on said lensing means.
- 26. The system of claim 24, wherein said illumination means comprises a laser and said multiple element passing means comprises a fly lens array.

30

- 27. The system of claim 24, wherein said illumination means comprises an arc lamp and said multiple element passing means comprises a pinhole array.
- 35

28. The system of claim 24, wherein said illumination means comprises a laser and said system further comprises a beam

20211343v1

The system of claim 26, wherein said fly lens arrangement 29. comprises a plurality of offset individual lenses.

system of claim 30, wherein said fly lens arrangement y aligned with respect to the pinhole mask. is substant

wherein said lensing system of claim 24, 10 31. comprises:

a first lens;

transmitter/reflector means;

an objective; and

a tube lens.

15

20

25

30

5

A method for inspecting a specimen, comprising the steps

denerating light energy;

selectively filtering and passing energy received from said illumination means using a multiple element arrangement; light energy onto said specimen; imparting

selectively filtering and passing energy reflected from said spedimen; and

performing a time delay and integration sensing function on received from said further selectively filtering light energy step.

The method of claim 32, further comprising the step of automatically focusing the light energy in said selectively wherein said automatic focusing comprises filtering step, candelling topographical during variations measuring and selective filtering.

20

20211343v1

4 Com the control of the control G... ("] 11 Ħ,